

# FOSSIL

STONE 6. 0







**BEIGE**

MATT  
STRUCTURED



**BROWN**

MATT  
STRUCTURED





**GREY**  
MATT  
STRUCTURED



**BLACK**  
MATT  
STRUCTURED







**SIZES**



**R9/R10**



60x60  
24"x24"



30x60  
12"x24"



30x30  
12"x12"

**FINISH**  
MATT  
STRUCTURED

**COLORS**  
BEIGE  
BROWN  
GREY  
BLACK

**DECORS**



**HEXAGON**  
30x30 - 12"x12"



**DIAMOND**  
30x30 - 12"x12"



**CUBE**  
30x30 - 12"x12"



**SLIM HEXAGON**  
30x30 - 12"x12"



**STRIPS**  
30x60 - 12"x24"



**STONE MOSAIC**  
30x60 - 12"x24"



**ZIG ZAG**  
30x60 - 12"x24"



**STONE STRIPS**  
30x60 - 12"x24"

## TECHNICAL CHARACTERISTICS

|                            |  | TECHNICAL FEATURES                | SPECIFICATION | VALUE REQUIRED                          | *SPACE VALUES          |
|----------------------------|--|-----------------------------------|---------------|---|------------------------|
| REGULARITY CHARACTERISTICS |  | LENGTH AND WIDTH                  | ISO 10545-2   | ±0.6%                                   | ±0.03%                 |
|                            |  | THICKNESS                         | ISO 10545-2   | ±5.0%                                   | -3%                    |
|                            |  | SQUARENESS                        | ISO 10545-2   | ±0.6%                                   | 0.04%                  |
|                            |  | STRAIGHTNESS OF THE EDGES         | ISO 10545-2   | ±0.5%                                   | 0.01%                  |
|                            |  | FLATNESS                          | ISO 10545-2   | ±0.5%                                   | 0.08%                  |
| STRUCTURAL CHARACTERISTICS |  | WATER ABSORPTION                  | ISO 10545-3   | ≤0.5%                                   | 0.06%                  |
|                            |  | BREAKING STRENGTH                 | ISO 10545-4   | ≥1300 N                                 | 2489 N                 |
|                            |  | MODULUS OF RUPTURE                |               | ≥35 N/mm <sup>2</sup>                   | 50.6 N/mm <sup>2</sup> |
| CHEMICAL CHARACTERISTICS   |  | CHEMICAL RESISTANCE               | ISO 10545-13  | TEST METHOD AVAILABLE<br>DECLARED VALUE | GA                     |
|                            |  | RESISTANCE TO STAINING            | ISO 10545-14  | TEST METHOD AVAILABLE<br>DECLARED VALUE | PASSED                 |
| SAFETY CHARACTERISTICS     |  | SLIP RESISTANCE INCLINED PLATFORM | DIN 51130     | TEST METHOD AVAILABLE                   | R9/R10                 |
|                            |  |                                   | DIN 51097     |   |                        |

## SIZE, WEIGHT AND PACKAGING

| SIZE  | PIECES/BOX | MQ/BOX | KG/BOX | MQ/PALLET | KG/PALLET | BOX/PALLET |
|-------|------------|--------|--------|-----------|-----------|------------|
| 60x60 | 4          | 1,44   | 32     | 57,6      | 1305      | 40         |
| 30x60 | 8          | 1,44   | 32     | 57,6      | 1305      | 40         |
| 30x30 | 11         | 0,99   | 22     | 53,46     | 1213      | 54         |

## FORMATS

|       | 60x60 | 30x60 | 30x30 |
|-------|-------|-------|-------|
| BEIGE |       |       |       |
| BROWN |       |       |       |
| GREY  |       |       |       |
| BLACK |       |       |       |

◇ MATT ■ STRUCTURED

THICKNESS

RECTIFIED

PLEASE PASTE YOUR NAMECARD HERE